



UL Online Certifications Directory

Fixed Condensed Aerosol Extinguishing System Units

FIREAWAY L L C

EX15004

11503 K-TEL DR

MINNETONKA, MN 55343 USA

Description	Part No.
Aerosol-generating extinguishing system unit	
Stat-X condensed aerosol generator, Model 30 E	15100
Stat-X condensed aerosol generator, Model 60 E	15110
Stat-X condensed aerosol generator, Model 100 E	15120
Stat-X condensed aerosol generator, Model 250 E	15130
Stat-X condensed aerosol generator, Model 500 E	15140
Stat-X condensed aerosol generator, Model 1000 E	15150
Stat-X condensed aerosol generator, Model 1500 E	15160
Stat-X condensed aerosol generator, Model 2500 E	15170
Aero-K condensed aerosol generator, Model G 30	11700
Aero-K condensed aerosol generator, Model G 60	11705
Aero-K condensed aerosol generator, Model G 100	11740
Aero-K condensed aerosol generator, Model G 250	11710
Aero-K condensed aerosol generator, Model G 500	11690
Aero-K condensed aerosol generator, Model G 1000	11770
Aero-K condensed aerosol generator, Model G 1500	14735
Aero-K condensed aerosol generator, Model G 2500	14740
Mounting bracket, for Models G 30, G 60, 30 E and 60 E	18001
Mounting bracket, for Models G 100 and 100 E	18005
Mounting bracket, for Models G 250, G 500, 250 E and 500 E	18010
Mounting bracket, for Models G 1000, G 1500, G 2500, 1000 E, 1500 E and 2500 E	18015
Stat-X Design, Installation, Operation and Maintenance Manual, dated 2009-09	19000
Stat-X Owner's Manual, dated 2009-09	19001
Aero-K Design, Installation, Operation and Maintenance Manual, dated 2009-10	19002
Aero-K Owner's Manual, dated 2009-10	19003

For Class A surface burning and Class B and C category hazards; not for use in hazardous (classified) locations.
 Temperature range -40 to 54°C.